

## CAMERA SPECIFICATION

<b>Image Device</b>	1/3" CMOS PC3089	
<b>TV System</b>	PAL	NTSC
<b>Effective Pixels</b>	756*504 pixels	
<b>Sensing Area</b>	4.80 mm*3.73mm	
<b>Scanning System</b>	2:1 Interlace	
<b>Sync. System</b>	Internal	
<b>Resolution</b>	500TV Lines	
<b>Horizontal Sync Frequency</b>	15.625 kHz	15.734 kHz
<b>Vertical Sync Frequency</b>	50 Hz	60 Hz
<b>Video Output</b>	1.0Vp-p, 75Ohm	
<b>Gamma Consumption</b>	0.45	
<b>AGC</b>	Auto	
<b>S/N Ratio</b>	Better than 46.5dB	
<b>White Balance</b>	Auto	
<b>Electronic Shutter</b>	1/60(NTSC)/1/50(PAL)~1/100,000 Seconds	
<b>BLC</b>	Auto	
<b>Storage Temperature</b>	-40℃ ~ 80℃, RH95%MAX	
<b>Operating Temperature</b>	-30℃ ~ 70℃, RH95%MAX	
<b>Power Supply</b>	DC12V	
<b>Waterproof rating</b>	IP69K	
<b>Viewing Angle</b>	120°	
<b>Audio</b>	Yes	
<b>Minimum Illumination</b>	0 Lux	
<b>Night vision distance</b>	15m	
<b>Image mode</b>	Mirror/Normal image switch	
<b>IR-CUT</b>	Yes	